

# RESTO<sup>TM</sup>

## Technical Product Data

a) Product Name	<b>ASBESTOS FREE MASONRY PAINT</b>
b) Reference Number	P.P.01.
c) Product Description	A highly decorative and protective coating. Formulated to give an asbestos free system that offers long term durability combining a high quality alkyd resin blended with a plasticiser, titanium and iron oxides are used to give excellent hiding power and pigmentation, reinforcing fibres and extenders provide the toughness and textured finish that enables the coating to withstand the elements.
d) Uses	A high build long life interior and exterior masonry coating.
e) Pack Sizes	25 Litres
f) Colour Range	White and 12 shades as per Resto colour card
g) Specific Gravity	1.21
h) Flash Point	Over 100°F
i) Solids	49% by volume
j) Spreading Rate @ D.R.A.T	1¼ litres / sq. metre = (2¾ imp. Gallons / 100 sq. ft.)
k) Drying Time	Touch dry 24 hours – Full cure 2 – 3 weeks
l) Overcoating time	24 hours
m) Lowest Application Temperature	5°C
n) Dry Recommended Application Thickness D.R.A.T	500 microns
o) Methods of Application	Spray
p) Recommended Preparation	See Preparation Sheet No. 1
q) Storage Life	1 Year
r) Thinner / Cleaner	White Spirit
s) Precautions	Stir well before use
t) Safety	Ensure the use of good filter masks when spraying. The use of Barrier Cream is recommended. Do not smoke or allow naked flames in vicinity of work. Extreme care must be taken when spraying in enclosed areas. Supply air fed masks. Rinse mouth and throat with water immediately, dilute stomach contents with water, obtain medical attention.

