

RESTOTM

Technical Product Data

a) Product Name	E.M.C.5
b) Reference Number	P.P.39.
c) Product Description	A high quality textured coating system based on a Thermoplastic resin incorporating butadiene and acrylate monomers, Titanium and other pigments. Offers excellent colour retention. Various size particles of Granicalcium are used to give an extremely durable coating.
d) Uses	A textured long life coating for masonry substrates.
e) Pack Sizes	20 Litres
f) Colour Range	12 Colours plus white
g) Specific Gravity	1.53
h) Flash Point	Over 23°C
i) Solids	51.0
j) Spreading Rate @ D.R.A.T	1.25 kg / m ²
k) Drying Time	Touch dry 24 hours – Full cure 2 – 3 weeks
l) Overcoating time	24 hour
m) Lowest Application Temperature	5°C
n) Dry Recommended Application Thickness D.R.A.T	295 microns
o) Methods of Application	Roller & Trowel Roller & Texturing Air Spraying Pressurised Pot
p) Recommended Preparation	See Preparation Sheet No. 7
q) Storage Life	1 Year
r) Thinner / Cleaner	White Spirit
s) Precautions	Stir well before use
t) Safety	Ensure the use of good filter masks when spraying. The use of barrier cream is recommended. Do not smoke or allow naked flames in the vicinity of work. Extreme care must be taken when spraying in enclosed areas.

