

RESTOTM



Technical Product Data

- a) Product Name **FLOOREX**
- b) Reference Number P.P.30
- c) Product Description
A single pack, satin finish floor maintenance coating with elastomeric characteristics, based on the internationally known Goodyear 'pliolite resin' technology. It has excellent resistance to alkali, acid, petrol, mineral and vegetable oils. It is formulated to exhibit a low tendency to peel, crack or blister.
- d) Instructions for Use
To obtain ultimate performance, all surface areas must be structurally sound and free from all friable materials, (paint, dirt, grease, etc.) Wear a good quality face mask when spraying.
- e) Preparation Procedure
Remove all contamination by: etch cleaning, detergent scrubbing, sanding or scarifying.
FLOOREX will overcoat most sound painted substrates.
- f) Mixing & Application Procedure
1) Mix thoroughly before use.
2) Apply by brush, roller or spray.
3) Overcoating time: 4 - 16 hours at 20° C
Cure time 24 - 36 hours for traffic.
4) On unsealed (painted) or porous substrates priming may be necessary, if so reduce first coat with 10-15% white spirit then follow on with a 2 coat system.
- g) Coverage
9m² per LT (one coat) dependent on porosity of substrate. Dry film thickness 50 microns (2 thou).
Specific gravity 1.25. Volume 45% Flash point 40° C
- h) Storage
12 months in original sealed tins.
- i) Health & Safety
FLOOREX is white spirit based which in general is quite harmless providing normal precautions are taken.
1) SKIN CONTACT - use white spirit or hand cleaner.
2) EYE CONTACT - wash out with glycerine.
3) INGESTION - should ingestion occur consult a doctor.
4) APPLICATION - ensure adequate ventilation.

