

RESTOTM

Technical Product Data

a) Product Name	HIGHBUILD E.M.C.8
b) Reference Number	P.P.40
c) Product Description	A high quality textured coating system based on a thermoplastic resin incorporating butadiene and acrylic monomers, titanium and iron oxide pigments. Offers excellent colour retention. Various size particles of granicalcium are used to give an extremely durable long-term coating.
d) Uses	A high build long-life coating for Masonry Substrates.
e) Pack Sizes	25 kilo drums
f) Colour Range	11 colours plus white
g) Specific Gravity	1.53
h) Flash Point	Over 23 °C
i) Solids	47-0
j) Spreading Rate @ D.R.A.T	3 kg / m ²
k) Drying Time	Touch Dry 24 hours. Full cure 2-3 weeks
l) Lowest Application Temperature	5 °C
m) Dry Recommended Application Thickness D.R.A.T	900 Microns
n) Methods of Application	Roller & Trowel. Roller & Texturing. Air Spray Pressurised pot.
o) Recommended Preparation	See Preparation Sheet No. 7
p) Storage Life	12 months
q) Thinner / Cleaner	White Spirit
r) Precautions	Ensure the use of good filter masks when spraying. The use of barrier cream is recommended. Do not smoke or allow naked flames in the vicinity of work. Extreme care must be taken when spraying in enclosed areas. Supply air fed masks.

