

RESTOTM

Technical Product Data

a) Product Name	HIGHBUILD W TEXTURE
b) Reference Number	P.P.45
c) Product Description	A high quality durable textured system based on an outstanding vinyl resin incorporating Titanium and Iron Oxide Pigments ensuring good colour retention. Various size particles of Granicalcium are used to give a long lasting finish for any Masonry Substrates.
d) Uses	A high build long-life coating for Masonry & Exterior Plywood Substrates.
e) Pack Sizes	14 & 21 kilo drums
f) Colour Range	6 colours plus white
g) Specific Gravity	1.65
h) Solids	74.2
i) Spreading Rate @ D.R.A.T	2.25kg- 3.00 kg Depending on Texture Finish & Substrate
j) Drying Time	Touch Dry 12 hours. Full cure 2-3 weeks
k) Lowest Application Temperature	5 °C
l) Dry Recommended Application Thickness D.R.A.T	900 Microns
m) Methods of Application	Roller & Trowel, Roller & Texturing, Air spray, Pressure Pot.
n) Recommended Preparation	See Preparation Sheet No. 1
o) Storage Life	1 year frost free storage
p) Thinner / Cleaner	Water
q) Precautions	Ensure the use of good filter masks when spraying, splashes in the eyes must be washed out at once with plenty of clean water. Barrier cream is recommended
r) Storage	Store in a frost free area, avoid high temperatures and direct sunlight.

