

RESTOTM

Technical Product Data

| | |
|--|--|
| a) Product Name | LOWBUILD S TEXTURE |
| b) Reference Number | P.P.47 |
| c) Product Description | A high quality textured coating system based on a thermoplastic resin incorporating Butadiene and Acrylate Monomers, Titanium and Iron Oxide Pigments. Offers excellent colour retention. Various size particles and Granicalcium are used to give an extremely durable long term coating. |
| d) Uses | A high build long-life coating for Masonry Substrates. |
| e) Pack Sizes | 15 litre drums |
| f) Colour Range | 6 colours plus white |
| g) Specific Gravity | 1.53 |
| h) Solids by Volume | 51.0 |
| i) Flash Point | Over 23 degrees C. |
| j) Spreading Rate | 1.0 kg/M ² |
| k) Drying Time | Touch Dry 24 hours. Full cure 2-3 weeks |
| l) Lowest Application Temperature 5 °C | |
| m) Dry Recommended Application Thickness D.R.A.T | 290 Microns |
| n) Methods of Application | Roller & Trowel, Roller & Texturing, Air spray, Pressure Pot. |
| o) Recommended Preparation | See Preparation Sheet 1 |
| p) Storage Life | 1 year |
| p) Thinner / Cleaner | White Spirit |
| q) Precautions | Ensure the use of good filter masks when spraying. The Use of Barrier Cream is recommended. DO NOT SMOKE or allow naked flames in the vicinity of work. Extreme care must be taken when spraying in enclosed areas. Supply Air Fed Masks. |

