

RESTOTM

Technical Product Data

a) Product Name	PRIMESEAL / TINTED STABILISER
b) Reference Number	P.P.21
c) Product Description	Primeseal has been specially formulated to provide a firm base for the top coat applications it is ideal for uncoated masonry substrates giving excellent adhesion to porous and chalking substrates. Primeseal is a pigmented primer it's extra hiding powers offer advantages over clear stabilising systems, once Primeseal has dried it offers a first class surface for emulsion type paints. It is especially resistant to alkaline and acid attack.
d) Uses	Stabilisation of wall surfaces for use under textured coatings and emulsion paints.
e) Pack Sizes	5 & 25 litre
f) Colour Range	Supplied on request
g) Specific Gravity	1.41
h) Solids	47
i) Flash Point	40 °C
j) Spreading Rate @ D.R.A.T.	3 Sq. metres / Litre
k) Drying Time	8 hours @ 20 °C
l) Overcoating Time	12 hours @ 20 °C
m) Lowest Application Temperature	5 °C
n) Dry Recommended Application Thickness D.R.A.T	225 Microns
o) Methods of Application	Brush, roller and spray.
p) Recommended Preparation	See Preparation Data Sheet No.1
q) Storage Life	6 months
r) Thinner / Cleaner	P.P.27
s) Precautions	The use of masks is recommended when spraying
t) Safety	Do not expose to naked flame. Do not smoke in work area

